



For substrate preparation prior to sealing with Alfix M-Silicon

- Improves bonding to ceramic tile edges
- Suitable for areas permanently exposed to water
- Designed for swimming pool application
- For interior and exterior use

Product

Fast acting, thin, clear liquid.
Contains solvents.

Coverage

Approx. 250 running metres per can.

Packaging

500 ml can

Preparation

Remove any excess residues from adhesive or grout down to original substrate by grinding.

For pool application bonding surfaces should always be primed.

Ensure joint widths ranging from 10-15 mm.

Bonding surfaces should be dry, clean and degreased. Vacuum and degrease using acetone or methylated spirit.

Instructions for use

Apply masking tape along tile edges. Apply Alfix P-Primer to both bonding surfaces in an even coat and allow primer to dry completely before any further treatment.

Cleaning

Residues from Alfix P-Primer on tools, equipment, etc should be cleaned immediately after use with methylated spirit. Once dried, P-Primer can only be removed by mechanical means.

Technical Enquiries

Product info:

- Alfix M-Silicon

Safety data sheet/COSH

For further informations, please consult our Technical Services Dep.

For latest update of this product info, visit alfix.com

Technical data

Working temperature	+5°C - +40°C
Drying time	Approx. 1 hour at +20°C
Shelf life	Min. 12 months in unopened container. Store cool.

