



- Gentle acidic cleaning agent for effective dissolving and removal of lime and surface fouling
- Does not attack chromium or stainless steel
- Removes cement film from new tilings
- Suitable for sanitary use

Product

Cleaning agent based on a mixture of phosphoric acid and active cleaning components.
For cleaning of sanitary areas

Coverage

1 litre per 20 – 40 m²

Packaging

1 litre and 2½ litres container

Applications

For removal of limescale deposits and cement film on ceramic tiles, quarry tiles, mosaics, vinyl, and stainless steel.

Do not use on marble and enamel.

Surface preparation

If any doubt regarding acid resistance of the surface, it is always recommendable to test the product on a less visible area or spot.

Instructions for use

Pre-wet the surface with clean water.

Dilute Alfix Lime and Grout remover with water 1:5 - 1:10.

Apply the solution to the surface using a sponge. Prevent running causing visible trails.

After a working time of 5- 10 minutes, scrub the surface and rinse thoroughly with clean water.

Allow min. 24 – 48 hours upon grouting before removal of cement film.

Technical enquiries

Product health and safety data /COSH

For further information, please consult our Technical Services Dept.

For latest update of this product info, visit www.alfix.com.

Technical data

pH-value	Concentrated: approx. 1.0 Diluted 1:10: approx. 2.0
Shelf life	Protect from frost Min. 12 months stored at +20°C

