

Cleaning and maintenance instructions for Alfix TopCoat Design

GB 08-2022



Before starting to use the floor

No sooner than 1 day after completing treatment with Alfix TopCoat Design, we recommend washing the floor twice with Alfix Floor Cleaner diluted in water in the ratio of 1 dl Alfix Gulvpleje to 10 litres hand-hot water.

You should leave at least 1 hour between the first and the second wash. There is no need to wash the floor with clean water afterwards.

Day-to-day maintenance of the floor

Wipe up any spillages on the floor before they dry, as this will minimise the risk of stains forming. Clean the floor with a cloth moistened in hand-hot water and firmly wrung out.

If necessary, clean with Alfix Floor cleaner mixed in a ratio of ¼–½ dl product to 10 litres hand-hot water.

Periodical freshening up/ maintenance of the floor

Depending on how heavy the daily foot traffic is, the floor will need to be freshened up/maintained at appropriate intervals using Alfix Floor cleaner diluted in water in the ratio of 1 dl Alfix Floor cleaner to 10 litres hand-hot water.

If the floor is very dirty, it may be necessary to clean it with Alfix Deep Cleaner diluted in water in the ratio of 1 part Alfix Deep cleaner to 10 parts hand-hot water.

Wash the floor with the mixture and leave it to take effect for 5–10 minutes.

Then work up the floor with a cloth and brush.

After this, wash the floor several times with clean water so as to remove all the Alfix Deep cleaner.

This process will also remove all traces of Alfix Floor cleaner, so you will need to build up the protective layer of Alfix Floor cleaner again as described above in the section entitled "Before starting to use the floor".

If you follow these cleaning and maintenance instructions carefully, you can be sure of always having a finely cared for Alfix TopCoat Design floor.

Produkter

- Alfix Floor cleaner
- Alfix Deep cleaner

